



## Tanker Filter 14" & 16"



### TANKER FILTER 14" & 16"

The Tanker range of basket filters and strainers are for use where flow can be interrupted to allow removal of element for cleaning. They have a very low profile and are **well suited to situations where there is limited space**. Tanker filters are of simple and robust cast iron construction with in line connections and are designed to be used on liquids.

**SPX Process Equipment**

Plenty House, Hambridge Road, Newbury, Berkshire, RG14 5TR

Telephone +44 (0)1635 42363 Facsimile +44 (0)1635 49758 Email [filters.plenty@processequipment.spx.com](mailto:filters.plenty@processequipment.spx.com) [www.plentyfiltration.com](http://www.plentyfiltration.com)



# Tanker Filter 14" & 16"



## STANDARD FEATURES

- Twin baskets giving high dirt holding capacity for longer running between cleaning
- Quick release covers eliminate the need of tools for maintenance
- No spillage on cover removal
- Smooth passages for low resistance and low pressure drops
- Feet on the body for easy mounting
- Cover and bridge linked for easy and quick access
- Flow is from inside the basket to outside to trap and retain all debris
- High basket area to pipeline CSA ratio of approximately 6:1 in most cases
- Can be fitted with coarse perforated baskets (2 mm as standard)

## DIMENSIONS

Size (Bore)	A	B	C	D	E	G	J	K	Weight	
In mm	mm	mm	mm	mm	mm	mm	in mm	mm	lb	kg
14 350	787	470	388	406	851	851	1 1/2" 547	571	1290	585
16 400	787	445	413	406	851	851	1 1/2" 547	571	1290	585

\* Vent is 3/8" BSPT

**Design Pressure:** 10 BARG @ 30°C

**Flanged ANSI 125FF** (can be drilled to PN10 or PN16)

